

MV-PD010003-06M-12C

Logistics Code Reading Set



Introduction

MV-PD010003-06M-12C logistics code reading set consists of industrial camera, lens, and light source. With barcode recognition technology, it can automatically locate and recognize barcode on package, and output barcode information. It is widely applicable to logistics distribution center, etc.

Available Model

MV-PD010003-06M-12C


Applicable Industry

Logistics code reading, warehouse sorting, etc.

Dimension

Key Feature

- Adopts code recognition technology.
- Supports acquisition and integration of data and images.
- Supports local data storage, uploading, and tracking.
- Adopts integrated structure to facilitate installation.
- Centralized light with high luminescence efficiency.
- Long service life time, and stable performance.
- Provides real-time and effective data for logistics related enterprises.



Unit: mm

Model	MV-PD010003-06M-12C
Performance	
Symbologies	1D codes: Code 39, Code 93, Code 128, Codabar, EAN
	2D codes: QR Code, Data Matrix
Focal length	12 mm
Best working distance	900 mm
Field of view	550 mm × 340 mm @10 mil
Depth of field	500 mm
Resolution	3072 × 2048
Max. frame rate	17 fps @3072 × 2048
Aperture	F2.8 to F16
Center illuminance	5800 lux @1000 mm
Uniformity	0.53
Luminous flux	2500 lm
Light source wavelength	420 nm to 730 nm
Color temperature	5700 K
Mono/color	Mono
Pixel format	Mono 8
Electrical features	
Data interface	Gigabit Ethernet
Digital I/O	6-pin connecting terminal provides power and I/O, including opto-isolated input × 1 (Line 0), and bi-directional non-isolated I/O × 1 (Line 2)
Power supply	24 VDC
Power consumption	20 W
Mechanical	
Dimension (without lens)	164.2 mm × 149.6 mm × 159.1 mm (6.5" × 5.9" × 6.3")
Weight (without lens)	Approx. 990 g (2.2 lb.)
Temperature	Working temperature: 0 °C to 50 °C (32 °F to 122 °F) Storage temperature: -30 °C to 70 °C (-22 °F to 158 °F)
Humidity	20% to 80% RH, non-condensing
General	
Client software	MVS, Code Platform
Operation system	32/64-bit Windows XP/7/10
Certification	CE, KC

Note:

- Do not directly touch cooling parts of the device to avoid scald.
- Do not debug the device for a long time in close distance to avoid scald.