

MV-SC6016M-00C**1.6 MP Mono Smart Camera**

MV-SC6016M-00C smart camera is developed based on high-performance embedded platform with strong calculation performance. It integrates VM functions and AI deep learning algorithm, and can use more than 140 algorithms. It adopts multiple interfaces for supporting external light source, display, mouse, etc.

**Key Features**

- Adopts AI deep learning algorithm to achieve OCR, object recognition, defect detection, etc.
- Integrates VM functions, and supports more than 140 algorithms.
- Adopts multiple interfaces, and supports multiple-channel I/O, light source, display, etc.
- Adopts high-performance CPU with faster calculation performance and high efficiency.
- Supports multiple communication protocols.
- Supports indicators displaying device status for easy debugging and maintenance.
- Supports ingress protection IP67.

Available Models

- V1.0: MV-SC6016M-00C-NNN
- V2.0: MV-SC6016M-00C-NNN/V2

Typical Application

- Consumer electronics
- Food and pharmaceutical
- Packaging
- Positioning and grabbing



Specification

Model	MV-SC6016M-00C-NNN		MV-SC6016M-00C-NNN/V2
Tool			
Function module	Vision Master Platform (include deep learning module)		
Communication protocol	TCP, UDP, MODBUS, Serial Port, PROFINET, EtherNet/IP, Fins, MC, FTP, etc.		
Camera			
Sensor type	CMOS, global shutter		
Pixel size	3.45 μm × 3.45 μm		
Sensor size	1/2.9"		
Resolution	1408 × 1024		
Max. frame rate	60 fps	120 fps	
Gain	0 dB to 15 dB		
Exposure time	16 μs to 1 sec	25 μs to 1 sec	
Pixel format	Mono 8		
Mono/color	Mono		
Platform			
Memory	8 GB		
Storage	64 GB		
Electrical features			
Data interface	Gigabit Ethernet (1000 Mbit/s)		
Digital I/O	17-pin M12 connector provides power and I/O, including opto-isolated input × 2 (Line 0/1), opto-isolated output × 2 (Line 4/5), configurable non-isolated input/output × 2 (Line 2/3), RS-232 × 1, and light source output (max. 30 W) × 1		
Extended interface	VGA × 1, and USB host × 1		
Power supply	24 VDC		
Power consumption	Avg. 12 W @ 24 VDC (without external light source) Avg. 42 W @ 24 VDC (with external light source) Max. 18 W @ 24 VDC (without external light source) Max. 48 W @ 24 VDC (with external light source)		
Mechanical			
Lens mount	C-mount		
Lens cap	Transparent lens cap		
Light source	Not included		
Indicator	Power indicator (PWR), network indicator (LNK), status indictor (STS), and user-defined indicator (U1/U2)		
Dimension	116.3 mm × 68.6 mm × 101.8 mm (4.6" × 2.7" × 4.0")		
Weight	Approx. 530 g (1.2 lb.)		
Ingress protection	IP67 (under proper installation of waterproof lens cap)		
Temperature	Working temperature: 0 °C to 50 °C (32 °F to 122 °F) Storage temperature: −30 °C to 70 °C (−22 °F to 158 °F)		
Humidity	20% RH to 95% RH (no condensation)		

Vibration resistance	Meets standard IEC 60068-2-6:2007. Device only (without installation bracket): 10 Hz to 55 Hz, 1.5 mm peak-to-peak amplitude, 2 hours per axis (X, Y, Z)*
Shock resistance	Meets standard IEC 60068-2-27:2008. Device only (without installation bracket): 30 g / 11 ms, half-sine wave, 500 shocks per axis (6 directions)*
General	
Certification	CE, KC

* After attaching the C-mount lens to camera, tighten the focus ring with set screws and reinforce it by applying UV adhesive around the ring.

Dimension

